RNP RWY10 – Initial – UC 104

Serial # / Procedure designator	Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [km]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed limit [kts]
1 / RNP RWY10	RNP APCH	IF	UC104	42°39'08.0"N /078°11'14.1"E	-	-	-	-	- / 7800	-220
2 / RNP RWY10	RNP APCH	TF	UC103	42°33'16.6"N /078°09'17.1"E	N	193.8 / 189	11.2	-	- / 7800	-220

RNP RWY10 – Initial – UC 107

Serial # / Procedure designator	Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [km]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed limit [kts]
1 / RNP RWY10	RNP APCH	IF	UC107	42°31'00.5"N/ 077°52'00.0"E	-	-	-	-	-/8000	-
2 / RNP RWY10	RNP APCH	TF	UC103	42°33'16.6"N/ 078°09'17.1"E	N	079.8 /075	24.0	-	-/7800	-220

RNP RWY10 – Common

Serial # / Procedure designator	Navigational performance	Path descriptor	Waypoint identifier	Waypoint coordinates	Fly-Over	True track [°] / Magnetic track [°]	Distance [km]	Turn direction	Upper limit [ft] / Lower limit [ft]	Speed limit [kts]	VPA (GPA) [°]/ TCH (RDH) [ft]
1 / RNP RWY10	RNP APCH	IF	UC103	42°33'16.6"N / 078°09'17.1"E	-	-	-	-	- / 7800	-220	-
2 / RNP RWY10	RNP APCH	TF	UC102	42°31'51.3"N / 078°17'04.9"E	N	103.8 / 99	10.9	-	@7200	-	-
3 / RNP RWY10	RNP APCH	TF	UC101	42°30'55.9"N / 078°22'07.0"E	Y	103.9 /099	7.1	-	-	-	-
4 / RNP RWY10	RNP APCH	CA	-	-	-	103.9 /099	-	-	@6300	-160	-
5 / RNP RWY10	RNP APCH	DF	UC105	42°37'42.5"N / 078°19'02.7"E	N	-	-	L	-	-	-
6 / RNP RWY10	RNP APCH	TF	UC104	42°39'08.0"N / 078°11'14.1"E	N	283.9 /279	11.0	-	- / 7800	-220	-
7 / RNP RWY10	RNP APCH	TF	UC092	42°40'59.5"N / 078°00'57.5"E	N	283.8 /279	14.5	-	-	-	-
8 / RNP RWY10	RNP APCH	TF	UC093	42°39'36.3"N / 077°49'54.5"E	N	260.4 /255	15.3	-	- / 8000	-	-
9 / RNP RWY10	RNP APCH	TF	UC107	42°31'00.5"N / 077°52'00.0"E	N	169.8 /165	16.2	-	- / 8000	-	-